

T2340



Tally

DASCOM's mid range serial matrix printers include the T2240/T2340 series products. These printers feature great ergonomics as the paper is front loaded rather than installed in the rear. With automatic top of form and zero tear the printers are easy to set up with no wasted forms.

The products are ideal for back office applications which include retail, local government, hospitals, warehousing and distribution. They include printing labels, shipping documents and multipart forms.

Highlights at a glance:

- High quality 24 pin printhead
- Front feed for easy paper loading and reliable paper transport
- Zero tear, paper park, automatic top of form for ease of use
- Wide range of emulations for easy connection to a wide range of hosts
- Manual feed: front in, front out; ideal for cheques, statements, registration cards

Narrow and wide format machines offer the choices of small footprint and diverse range of forms.

In line with market demands, the new printers are quieter and easier to use than competitive products in their class. All products support graphics and barcodes.

Available Configuration:

- **T2340/24** 24 pin version

T2340

Print Speed	440 cps (Fastest Draft); 409 cps (Draft), 92 cps (LQ) at 10 cpi (24 pin)
Resolution	up to 360 x 360 dpi (24 pin)
Throughput (ECMA 132)	368 pages per hour (24 pin)
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	3, 4, 6, 8, 12 lpi
Printhead Life	300 million strokes per pin
Standard Memory	64 kB
Optional Memory	128 kB (Factory build)
Standard Connectivity	Parallel (Bi-directional)
Standard Emulation	IBM ProPrinter XL, Epson LQ2250, MTPL + Barcode)
Fonts	HS Draft, Draft, Roman, Sans Serif, Prestige, Elite, Script, OCR-A/B
Consumables	Ribbon: 4 million characters
Standard Paper Handling	Push tractor and cut sheet insertion
Optional Paper Handling	2 nd Push tractor
Number of Copies	1 original + 3 copies
Paper Type	Cut sheets, continuous forms, multi-part forms
Paper Weight	60-120 g/m ²
Paper Size	Width: 3" to 16.5"; Length: 3" to 22"
Physical Weight	24.25 lbs kg
Physical Size	24.6" x 9.6" x 7.8" (W x D x H)
Noise Level (ISO 7779)	53 dB(A)
Power Voltage	120 V and 220 V models available
Power Consumption	55 Watt Printing
Temperature	+10° to +35° C; 20% to 80% humidity (not condensing)
Workload	14.000 pages per month
MTBF	12.500 hours
Warranty	1 year return to depot
Drivers	Windows 2000/XP/Vista/7 and Server 2003/2008; SAP

DASCOM Americas Corporation

421 West Main Street
Waynesboro, Virginia
USA 22980-3606
Tel: 877 434 1377
www.dascom.com

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 