

T2540



Tally

DASCOM's mid range T2540 serial matrix printers are designed for applications where fast throughput and flexible paper management are vital.

Forms are easy to load as the paper is loaded either at the front or the rear of the printer. For precise paper control and to enable feeding of continuous forms, the push tractor can also be used as a pull tractor.

The printer features a long life 9 pin print head providing compatibility with Oki and Epson 9 pin emulations. All printers support graphics and barcodes systems.

Highlights at a glance:

- Print speeds up to 576 cps
- 136 columns
- Tractor feed and Manual insertion; ideal for invoices, reports, general office documents
- Reliable and durable
- USB and Parallel standard
- Optional integrated Ethernet (10/100BaseT) and Serial RS232 available
- Quick change, long life ribbon in this class

With auto switching USB, parallel interfaces as standard and an optional Ethernet or serial interface, these new dot matrix printers offer a cost effective solution.

With high print speeds of up to 576 characters per second (cps) and the ability to handle different types of print media, including labels, invoices, reports and multi part forms, they are well suited for back office applications, including retail, local government, healthcare, warehousing and distribution.

Available Configuration:

- **T2440/9** 9 pin version/136 column
- **T2440/24** 24 pin version/136 column

T2540

Print Speed	533 cps (Fastest Draft); 533 cps (Draft), 100 cps (NLQ) at 10 cpi (9 pin) 576 cps (Fastest Draft); 480 cps (Draft), 133 cps (LQ) at 10 cpi (24 pin)
Resolution	up to 144 x 240 (9 pin) up to 360 x 360 dpi (24 pin)
Throughput (ECMA 132)	395 pages per hour
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	1, 2, 3, 4, 6, 8, 12 lpi
Printhead Life	400 million characters
Memory	256 kB
Standard Connectivity	Parallel (Bi-directional) and USB 2.0
Standard Emulation	IBM ProPrinter XL24, Epson ESC P (9 pin) IBM ProPrinter XL24E, Epson ESC P/2 (24 pin)
Fonts	HS Draft, Draft, Courier, Quadrato, OCR-A/B (9 pin) HS Draft, Draft, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B (24 pin)
Consumables	Ribbon: 8 million characters
Standard Paper Handling	Push tractor (rear) or pull tractor (front) and cut sheet insertion
Number of Copies	1 original + 5 copies (9 pin) 1 original + 4 copies (24 pin)
Paper Type	Cut sheets, continuous forms, multi-part forms
Paper Weight	60-120 g/m ²
Paper Size	Width: 76 to 406 mm
Physical Weight	18.73 lbs
Physical Size	21.3" x 13" x 5.3" (W x D x H)
Noise Level (ISO 7779)	52 dB(A)
Power Voltage	120 V and 220 V models available
Power Consumption	51 Watt Printing; <7 W Sleep Mode
Temperature	+10° to +40° C; 20% to 85% humidity (not condensing)
Print Volume	20.000 pages per month
MTBF	15.000 hours
Warranty	1 year return to base
Drivers	Windows 2000/XP/Vista/7 and Server 2003/2008

DASCOM Americas Corporation

421 West Main Street
Waynesboro, Virginia
USA 22980-3606
Tel: 877 434 1377
www.dascom.com

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 